

Silkon

FLOWMIX PC 100

Flowmix PC100 is an advanced technology based low viscosity Super plasticiser, based on Polycarboxylic technology for Precast Concrete and early strength concrete elements or structure. Supercast PC100 complies to IS:9103:1999 as a Superplasticizer and ASTM C 494 Type F and G depending on dosage.

Advantages

Flowmix PC100 is a high performance precast super plasticizer intended for applications where reduction in cycle time and early strength are required, and it has been developed for use in Precast concrete elements like Hollow core slabs Block, Cement Tiles ,Kerbstones , Edgings ,other items for garden landscape design ,Building blocks , bricks etc

- Concrete requiring high early strength without steam curing.
- High performance concrete.
- Low viscosity admixture suitable for precast elements Suitable for concrete having cement replacements and low water cement ratio.
- Provides high early strength without increase in cement content or reduction in workability.
- Ideal for precast concrete production Early de-shuttering will result in increased productivity.
- Improves surface finish Minimizes damage due to early handling.
- Better resistance to Carbonation.
- Reduces Shrinkage and Creep.
- Reduces efflorescence.

Technical support

Brij additives provides on-site technical service for assistance and advice on mix design, admixture selection, evaluation trials etc.

Health and safety

Flowmix PC100 does not fall into the hazard classifications of current regulations. However, it should not be swallowed or allowed to come in contact with skin or eyes. Suitable protective gloves and goggles should be worn.

About

Flowmix PC 100 is a unique combination of the latest generation super plasticisers, based on polycarboxylic ether polymer with long side chains and short main chains. This greatly improves cement dispersion and as well as facilitate quick start of hydration process. At the start of the mixing process an electrostatic dispersion occurs but the cement particles capacity to separate and disperse.



This mechanism considerably reduces the water demand in flowable concrete. Flowmix PC100 is a strong super plasticiser allowing production of consistent concrete properties at required dosage.

Properties

Appearance	Light yellow to Brownish colored Liquid
pH	Minimum 6.0
Relative density	1.09 ± 0.02
Chloride Ion content	As per BS EN: 480-10-1997(Product contains a chemical which interferes in the procedure as per IS 9103)

Note: The uniformity parameters like specific gravity, pH, chloride content etc. will vary for specific customer requirements and mix design. Please refer our MTC issued for specific product configuration for measuring our product parameters that will be constantly and consistently administered

Storage

Flowmix PC100 has a minimum shelf life of 12 months provided the temperature is kept within the range of 2°C to 40°C.

Registered Office:

Mayadevi Gaunpalika-5,
Bhairahawa, Rupandehi-Nepal
☎ +977-71-412050

✉ info@brijadditives.com

Corporate Office:

House No. 301, Ward No.1
Lalupate Marg, Hattisar-Nepal
☎ +977-01-5970708

🌐 www.brijadditives.com



Packaging

Flowmix PC100 is available in 250 kg drums and bulk tankers.

Over Dosages side effects

The optimum dosage of Flowmix 100 to meet specific requirement should always be determined by trials using the materials and conditions that will be experienced in use. The normal dosage range is between 0.2 to 1.5 ltrs/100 kg of cementitious material. Dosage beyond limits can be used to meet particular mix requirements in consultation with Brij additives technical department. Over dosage may cause delay in the setting time and segregation.

Cleaning and disposal

Spillage of Flowmix PC100 should be absorbed onto sand, earth or vermiculite and transferred to suitable container. Remnants should be hosed down with large quantity of water. The disposal of excess or waste material should be carried out in accordance with local legislation under the guidance of the local waste regulatory authority

Fire

Flowmix PC100 is water based and nonflammable.



ADMIXTURE
SOLUTIONS



ACCELERATOR



INDUSTRIAL
PRODUCT



WATERPROOF &
REPAIR SOLUTIONS



TILE
ADHESIVE

BRIJ ADDITIVES PVT. LTD.

BRIJ
ADDITIVES
EXPERT'S CHOICE

Registered Office:

Mayadevi Gaunpalika-5,
Bhairahawa, Rupandehi-Nepal

+977-71-412050

info@brijadditives.com

Corporate Office:

House No. 301, Ward No. 1
Lalupate Marg, Hattisar-Nepal

+977-01-5970708

www.brijadditives.com



ISO 9001:2015
Certified Company

Disclaimer: The product information & application details given by the company & its agents has been provided in good faith & is meant to serve only as a general guideline during usage. Users are advised to carry out tests and take trials to ensure on suitability of products meeting their requirements prior to full scale usage of our products. Since the correct identification of the problems, quality of the other materials used and on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The Company does not assume any liability or any consequences for damage or unsatisfactory results, arising from the use of our products.